

STAINLESS STEEL

Miniature Thrust Ball Bearing

Part No.: SF2-6

Size: 2 x 6 x 3 mm




Flat Washer
(No Raceway in Washer)

BASIC INFORMATION

For Shaft Diameter: 2 mm
Bore Dia (d): 2 mm
Bore Dia Tolerance: -0.008 mm to 0

For Housing ID: 6 mm
Outer Dia (D): 6 mm
Outer Dia Tolerance: -0.008 mm to 0

Height (B): 3 mm
Height Tolerance: -0.12 mm to 0



Washer: Stainless Steel SUS440C SUS304 SUS420

Cage: Stainless Steel SUS304 SUS420 Bronze

Ball: Stainless Steel SUS440C SUS304 SUS420

Ball Size: 1.000 mm

Ball Qty: 6 pieces

Dynamic Load Rating (Cr) (Newtons): 105

Static Load Rating (Cor) (Newtons): 75

Max Speed (Grease) (X1000 RPM): 14.4

Max Speed (Oil) (X1000 RPM): -

Lubrication: Required

Working Temperature: -30° to 110 °C

Weight (grams): 0.60

RoHS: Compliant



Flat Washer
(No Raceway in Washer)

This bearing print is for technical reference
and is displaying on www.clibearings.com ONLY!

PART
NO.

SF2-6
Stainless Steel Miniature Thrust Ball Bearing

PART
SIZE

Metric
2 x 6 x 3 mm

CLI BEARINGS CO., LTD.

www.clibearings.com
sales@clibearings.com

