

STAINLESS STEEL

Miniature Thrust Ball Bearing

Part No.: **SF4-10**

Size: **4 x 10 x 4 mm**




Flat Washer
(No Raceway in Washer)

BASIC INFORMATION

For Shaft Diameter: 4 mm
Bore Dia (d): 4 mm
Bore Dia Tolerance: -0.008 mm to 0

For Housing ID: 10 mm
Outer Dia (D): 10 mm
Outer Dia Tolerance: -0.008 mm to 0

Height (B): 4 mm
Height Tolerance: -0.12 mm to 0



Washer: Stainless Steel SUS440C SUS304 SUS420

Cage: Stainless Steel SUS304 SUS420 Bronze

Ball: Stainless Steel SUS440C SUS304 SUS420

Ball Size: 1.588 mm

Ball Qty: 6 pieces

Dynamic Load Rating (Cr) (Newtons): 592

Static Load Rating (Cor) (Newtons): 522

Max Speed (Grease) (X1000 RPM): 5.4

Max Speed (Oil) (X1000 RPM): -

Lubrication: Required

Working Temperature: -30° to 110 °C

Weight (grams): 2.00

RoHS: Compliant



Flat Washer
(No Raceway in Washer)

This bearing print is for technical reference
and is displaying on www.clibearings.com ONLY!

**PART
NO.**

SF4-10
Stainless Steel Miniature Thrust Ball Bearing

**PART
SIZE**

Metric
4 x 10 x 4 mm

CLI BEARINGS CO., LTD.

www.clibearings.com
sales@clibearings.com



© 2020 • All Rights Reserved • CLI BEARINGS®