

STAINLESS STEEL

Miniature Thrust Ball Bearing

Part No.: **SF7-15GW**

Size: **7 x 15 x 5 mm**



*Grooved Raceway
in Washer*

BASIC INFORMATION

For Shaft Diameter: 7 mm

Bore Dia (d): 7 mm

Bore Dia Tolerance: -0.008 mm to 0


For Housing ID: 15 mm

Outer Dia (D): 15 mm

Outer Dia Tolerance: -0.008 mm to 0

Height (B): 5 mm

Height Tolerance: -0.12 mm to 0



Washer: Stainless Steel SUS440C SUS304 SUS420

Cage: Stainless Steel SUS304 SUS420 Bronze

Ball: Stainless Steel SUS440C SUS304 SUS420

Ball Size: 3.000 mm

Ball Qty: 8 pieces

Dynamic Load Rating (Cr) (Newtons): 1980

Static Load Rating (Cor) (Newtons): 1800

Max Speed (Grease) (X1000 RPM): 3.24

Max Speed (Oil) (X1000 RPM): -

Lubrication: Required

Working Temperature: -30° to 110 °C

Weight (grams): 6.5

RoHS: Compliant



*Grooved Raceway
in Washer*

This bearing print is for technical reference
and is displaying on www.clibearings.com ONLY!

PART
NO.

SF7-15GW

Stainless Steel Miniature Thrust Ball Bearing

PART
SIZE

Metric

7 x 15 x 5 mm

CLI BEARINGS CO., LTD.

www.clibearings.com
sales@clibearings.com



© 2020 • All Rights Reserved • CLI BEARINGS®