

STAINLESS STEEL

Miniature Thrust Ball Bearing

Part No.: **SF4-10M**

Size: **4 x 10 x 4 mm**




*Grooved Raceway
in Washer*

BASIC INFORMATION

For Shaft Diameter: 4 mm
Bore Dia (d): 4 mm
Bore Dia Tolerance: -0.008 mm to 0

For Housing ID: 10 mm
Outer Dia (D): 10 mm
Outer Dia Tolerance: -0.008 mm to 0

Height (B): 4 mm
Height Tolerance: -0.12 mm to 0



Washer: Stainless Steel ☐ SUS440C ☐ SUS304 ☐ SUS420

Cage: Bronze

Ball: Stainless Steel ☐ SUS440C ☐ SUS304 ☐ SUS420

Ball Size: 1.588 mm

Ball Qty: 6 pieces



*Grooved Raceway
in Washer*

Dynamic Load Rating (Cr) (Newtons): 592

Static Load Rating (Cor) (Newtons): 522

Max Speed (Grease) (X1000 RPM): 5.4

Max Speed (Oil) (X1000 RPM): -

Lubrication: Required

Working Temperature: -30° to 110 °C

Weight (grams): 1.50

RoHS: Compliant

This bearing print is for technical reference
and is displaying on www.clibearings.com ONLY !

PART
NO.

SF4-10M

Stainless Steel Miniature Thrust Ball Bearing

PART
SIZE

Metric

4 x 10 x 4 mm

CLI BEARINGS CO., LTD.

www.clibearings.com
sales@clibearings.com



© 2020 • All Rights Reserved • CLI BEARINGS ®