

Miniature Thrust Ball Bearing

Part No.: **F8-16M**

Size: **8 x 16 x 5 mm**



*Grooved Raceway
in Washer*

BASIC INFORMATION

For Shaft Diameter: 8 mm
Bore Dia (d): 8 mm
Bore Dia Tolerance: -0.008 mm to 0

For Housing ID: 16 mm
Outer Dia (D): 16 mm
Outer Dia Tolerance: -0.008 mm to 0

Height (B): 5 mm
Height Tolerance: -0.12 mm to 0

Washer: chrome steel SAE52100

Cage: ☐ Steel ☐ Bronze

Ball: chrome steel SAE52100

Ball Size: 3.000 mm

Ball Qty: 9 pieces

Dynamic Load Rating (Cr) (Newtons): 2500

Static Load Rating (Cor) (Newtons): 3000

Max Speed (Grease) (X1000 RPM): 4


Max Speed (Oil) (X1000 RPM): 8

Lubrication: Required

Working Temperature: -30° to 110 °C

Weight (grams): 4.50

RoHS: Compliant



*Grooved Raceway
in Washer*

This bearing print is for technical reference
and is displaying on www.clibearings.com ONLY!

PART
NO.

F8-16M
Miniature Thrust Ball Bearing

PART
SIZE

Metric
8 x 16 x 5 mm

CLI BEARINGS CO., LTD.

www.clibearings.com
sales@clibearings.com



© 2020 • All Rights Reserved • CLI BEARINGS ®